

Y.B.

## L<sup>A</sup>T<sub>E</sub>X Class yb-book\*

Yegor Bugayenko  
yegor256@gmail.com

2026-05-06, 0.9.0

## 1 Introduction

The class yb-book was devised to assist the author in producing [his books](#) and in publishing them [on Amazon](#). Others are welcome to employ it for their own books. The procedure is straightforward:

```
\documentclass{yb-book}
\renewcommand*\thetitle{New Book About OOP}
\renewcommand*\theauthor{Jeff Lebowski}
\renewcommand*\thevolume{1}
\renewcommand*\theversion{1.0}
\begin{document}
\ybPrintTitlePage
\chapter{First One}
\section{About Something Interesting}
Hello, world!
\end{document}
```

Suggestions for additional options and commands are welcome; nevertheless, the style of the author's books is intentionally as plain as possible, eschewing formatting to the greatest extent practicable. The reasoning is set out [here](#).

## 2 Options

Several class options are available:

**compact** This package option is to be used when the text is required in a more compact form, occupying less vertical space. It proves convenient for works of fiction. The author employs it to render the [Code Ahead](#) book.

**sparse** Under this package option, every section commences on a new page.

---

\*The sources are on GitHub at [yegor256/yb-book](#)

- manuscript** Whenever the format is not intended for Amazon printing but for some other purpose (the page size being A4), this option proves convenient. The author likewise employs it whenever the book is to be rendered for printing on paper for review purposes.
- authordraft** This option is appropriate when the document is a draft for reviewers (the page size being A4) and a watermark together with a compact form of the content is desired. The option is used in conjunction with the `\thereviewer{}` command, which may be redefined to embed the name of the reviewer within the watermark. This serves as a deterrent to theft of the book:

```
\documentclass[authordraft]{yb-book}
\renewcommand*\thereviewer{Walter Sobchak}
\begin{document}
Hello, world!
\end{document}
```

### 3 Meta Commands

A number of commands may be redefined within the preamble:

```
\documentclass{yb-book}
\newcommand*\thetitle{My New Book About OOP}
\newcommand*\theauthor{Yegor Bugayenko}
\newcommand*\thevolume{1}
\newcommand*\thedata{24 Feb 2022}
\newcommand*\theversion{1.4}
\newcommand*\thereviewer{Jeff Lebowski}
\begin{document}
... the content goes here ...
\end{document}
```

### 4 Printers

A number of printers are provided—commands that render substantial blocks of text in the expected format:

- `\ybPrintTitlePage` Prints the first page of a book. At minimum, `\thetitle` and `\theauthor` must be defined:

```
\documentclass{yb-book}
\renewcommand*\thetitle{My New Book}
\renewcommand*\theauthor{Yegor Bugayenko}
\begin{document}
\ybPrintTitlePage
.. the rest of the book goes here
\end{document}
```

- `\ybPrintTOC` Prints the table of contents.

- `\ybQuote` Prints a side quote:

```
\documentclass{yb-book}
```

```

\begin{document}
Hello, world!
\ybQuote{Never tell the truth to people who
are not worthy of it}{Mark Twain}{}
\end{document}

```

A warning is emitted to the log whenever the quotation falls very close to the top or the bottom of a page, since the underlying `wrapfig` environment behaves poorly in such positions.

`\ybPrintBibliography` Prints the list of bib references.

`\ybPrintIndex` Prints index with an optional name of the section (instead of “Index”):

```

\documentclass{yb-book}
\begin{document}
Hello, world!
\ybPrintIndex[Recommended Books]
\end{document}

```

## 5 Implementation

First, we parse package options:

```

1 \RequirePackage{pgfopts}
2 \pgfkeys{
3   /yb/.cd,
4   apa/.store in=\yb@apa,
5   authordraft/.store in=\yb@authordraft,
6   compact/.store in=\yb@compact,
7   manuscript/.store in=\yb@manuscript,
8   colored/.store in=\yb@colored,
9   sparse/.store in=\yb@sparse,
10 }
11 \ProcessPgfPackageOptions{/yb}

```

Then, depending on the options like `authordraft` and `manuscript`, we preset options of the class `book` and then load it:

```

12 \makeatletter
13 \ifdefined\yb@authordraft
14   \PassOptionsToClass{11pt}{book}
15   \PassOptionsToClass{oneside}{book}
16 \else
17   \ifdefined\yb@manuscript
18     \PassOptionsToClass{12pt}{book}
19     \PassOptionsToClass{oneside}{book}
20   \else
21     \PassOptionsToClass{11pt}{book}
22     \PassOptionsToClass{twoside}{book}
23   \fi
24 \fi
25 \makeatother
26 \LoadClass{book}

```

Then, we load `href-ul` to underline links correctly:

```

27 \RequirePackage{href-ul}

```

Then, we load [cleveref](#) for the `\cref` command:

```
28 \PassOptionsToPackage{capitalize}{cleveref}
29 \RequirePackage{amsmath}
30 \RequirePackage{cleveref}
31 \crefformat{section}{\S#2#1#3}
```

Then, we require XeTeX or LuaTeX, because the class sets [CMU Concrete](#) as the default main font through [fontspec](#), which only works under those engines. If the document is compiled with pdfTeX, we stop with an explicit error rather than fall back silently. We pass the OTF file names directly to `\setmainfont` so that `kpathsea` locates them inside the TeX tree, without relying on a system-wide fontconfig database (which is absent in many CI containers):

```
32 \RequirePackage{iftex}
33 \ifPDFTeX
34   \ClassError{yb-book}{%
35     {This class requires XeTeX or LuaTeX}%
36     {Compile with xelatex or lualatex; pdflatex is not supported.}%
37   \endinginput
38 \fi
39 \RequirePackage{fontspec}
40 \setmainfont{cmunorm.otf}[
41   BoldFont = cmunobx.otf,
42   ItalicFont = cmunoti.otf,
43   BoldItalicFont = cmunobi.otf,
44 ]
```

`geometry` Then, using `geometry`, we set up page layout:

```
45 \RequirePackage{geometry}
46 \geometry{
47   paperwidth=6in, paperheight=9in,
48   bindingoffset=0.25in,
49   left=0.75in, right=0.75in, top=0.75in, bottom=1.25in}
50 \makeatletter
51 \ifdefined\yb@authordraft
52   \geometry{a4paper, margin=1in, left=1.5in}
53 \else
54   \ifdefined\yb@manuscript
55     \geometry{a4paper, margin=1.2in}
56   \fi
57 \fi
58 \makeatother
```

Then, we load [anyfontsize](#) to enable all sizes of fonts:

```
59 \RequirePackage{anyfontsize}
```

Then, we load [tikz](#) for graphics:

```
60 \RequirePackage{tikz}
61 \usetikzlibrary{positioning}
62 \usetikzlibrary{shapes}
63 \usetikzlibrary{fit}
```

Then, we load [chngcntr](#) for something else:

```
64 \RequirePackage{chngcntr}
65 \counterwithout{footnote}{chapter}
```

Then, we load [lastpage](#) to enable rendering of the last page number:

```
66 \RequirePackage{lastpage}
```

Then, we load [paralist](#) for inline enumeration:

```
67 \RequirePackage{paralist}
```

Then, we load [xcolor](#) for colors:

```
68 \RequirePackage{xcolor}
```

Then, we load [graphicx](#) to enable graphic files inclusion:

```
69 \RequirePackage{graphicx}
```

Then, we load [enumitem](#) for inline enumeration:

```
70 \PassOptionsToPackage{inline}{enumitem}
```

```
71 \RequirePackage{enumitem}
```

```
72 \setlist{nosep}
```

Then, we load [float](#) for floating figures:

```
73 \RequirePackage{float}
```

Then, we load [xfp](#) and [xifthen](#) for if-then-else:

```
74 \RequirePackage{xfp}
```

```
75 \RequirePackage{xifthen}
```

Then, we load [csquotes](#) for better rendering:

```
76 \PassOptionsToPackage{autostyle=try}{csquotes}
```

```
77 \RequirePackage{csquotes}
```

`\pagestyle` Then, we set the layout of a page to plain:

```
78 \pagestyle{plain}
```

`setspace` Then, using `setspace` package we set the spacing between lines in the text, depending on the package options:

```
79 \RequirePackage{setspace}
```

```
80 \setstretch{1.2}
```

```
81 \makeatletter
```

```
82 \ifdefined\yb@compact\setstretch{1.0}\fi
```

```
83 \ifdefined\yb@manuscript\setstretch{1.1}\fi
```

```
84 \ifdefined\yb@authordraft\setstretch{1.4}\fi
```

```
85 \makeatother
```

`biblatex` Then, we configure `biblatex` for citation management:

```
86 \PassOptionsToPackage{indexing=cite,
```

```
87 natbib=true,maxnames=2,minnames=1,doi=true,
```

```
88 url=false,isbn=false}{biblatex}
```

```
89 \makeatletter
```

```
90 \ifdefined\yb@apa
```

```
91 \PassOptionsToPackage{style=authoryear}{biblatex}
```

```
92 \else
```

```
93 \PassOptionsToPackage{style=numeric}{biblatex}
```

```
94 \fi
```

```
95 \makeatother
```

```
96 \RequirePackage{doi}
```

```
97 \RequirePackage{biblatex}
```

```
98 \DeclareCiteCommand{\citetracker}
```

```
99 {\boolfalse{citetracker}}%
```

```

100     \boolfalse{pagetracker}%
101     \usebibmacro{prenote}}
102   {\ifciteindex
103     {\indexnames{labelname}}
104     {}%
105     \printfield[citetitle]{labeltitle}}
106   {\multicitedelim}
107   {\usebibmacro{postnote}}
108 \DeclareCiteCommand*{\citetitle}
109   {\boolfalse{citetracker}%
110     \boolfalse{pagetracker}%
111     \usebibmacro{prenote}}
112   {\ifciteindex
113     {\indexnames{labelname}}
114     {}%
115     \printfield[citetitle]{title}}
116   {\multicitedelim}
117   {\usebibmacro{postnote}}

```

`condensed` Then, we define `condensed` environment for snippets:

```

118 \newenvironment{condensed}
119   {\beginngroup%
120     \addfontfeature{LetterSpace=-15}%
121     \lstset{columns=fixed,basewidth=0.45em}}
122   {\endgroup}

```

`microtype` Then, we include `microtype` for better rendering:

```

123 \makeatletter
124 \ifdefined\yb@authordraft
125   \PassOptionsToPackage{nopatch=footnote}{microtype}
126 \else
127   \PassOptionsToPackage{nopatch=footnote,protrusion=true}{microtype}
128 \fi
129 \makeatother
130 \RequirePackage{microtype}

```

`\section` Then, we redefine the `\section` command:

```

131 \makeatletter
132 \let\yb@oldsection\section
133 \def\yb@secstart{\ifdefined\yb@sparse\newpage\fi}
134 \ifdefined\yb@authordraft
135   \PassOptionsToPackage{medium}{titlesec}
136   \RequirePackage{titlesec}
137 \else
138   \PassOptionsToPackage{raggedright}{titlesec}
139   \RequirePackage{titlesec}
140   \titlespacing{\section}{0em}{2em}{1em}
141   \renewcommand\section{\yb@secstart\yb@oldsection}
142 \fi
143 \ifdefined\yb@compact
144   \renewcommand\section{\yb@secstart\vspace{2em}\yb@oldsection}
145 \fi
146 \makeatother

```

Then, we do small tweaking:

```

147 \makeatletter
148 \renewcommand\@makefnmark[1]{%
149   \raggedright%
150   \parindent=1em%
151   \noindent\hb@xt@1.8em{\hss\@makefnmark}\#1}
152 \makeatother

```

Then, if it's an authordraft, we put a watermark comment:

```

153 \makeatletter
154 \ifdefined\yb@authordraft
155   \PassOptionsToPackage{absolute}{textpos}
156   \RequirePackage{textpos}
157   \TPGrid{16}{16}
158   \RequirePackage{fancyhdr}
159   \pagestyle{fancy}
160   \renewcommand\headrulewidth{0em}
161   \renewcommand\footrulewidth{0em}
162   \setlength{\headheight}{3em}
163   \fancyhf{}
164   \fancyhead[L,C,L0,C0]{}
165   \fancyhead[R,R0]{
166     \begin{textblock}[16][0.5,0.5](8,8)%
167       \tikz \node[minimum width=16\TPHorizModule] {%
168         \fontsize{64}{64}\selectfont\bfseries%
169         \rotatebox{45}{
170           \tikz \node
171             [fill=gray!6, font=\ttfamily\color{white}]
172             {it is a draft};%
173         }%
174       };%
175     \end{textblock}%
176     \begin{textblock}[4](11.5,1)%
177       \tikz \node [color=gray, rotate=270,
178         font=\ttfamily\scriptsize, text width=24em] at (0,0) {%
179         Copyright \textcopyright{} \the\year{} by \theauthor{}.
180         All rights reserved. No part of the contents of
181         this book may be reproduced or transmitted in any
182         form or by any means without the written permission
183         of the publisher. This particular manuscript is
184         printed for \textbf{\thereviewer{}} and may be used only
185         for one-time review. The manuscript has to be destroyed
186         after the review.%
187       };
188     \end{textblock}
189   }
190   \fancyfoot[C,C0,C]{\small\ttfamily%
191     page \thepage{} of \pageref{LastPage}}
192 \fi
193 \makeatother

```

`\maketitle` Then, we redefine the `\maketitle` command:

```

194 \renewcommand\maketitle{
195   {\LARGE\textbf{\thetitle}}

```

```

196  \[1em]
197  by \theauthor{}
198  \[4em]
199  \ifx\thevolume\empty\else%
200    Volume \thevolume{}\
201  \fi
202  \ifx\thedata\empty\else%
203    Rendered on \thedata{}\
204  \fi
205  \ifx\theversion\empty\else%
206    Ver. \theversion{}
207  \fi
208 }

```

`\incolor` Then, we define the `\incolor` command:

```

209 \makeatletter
210 \newcommand\incolor[2]{\ifdefined\yb@colored\textcolor{#1}{#2}\else#2\fi}
211 \makeatother

```

`\ix` Then, we define the `\ix` command:

```

212 \newcommand\ix[2][]{%
213   \incolor{brown}{#2}%
214   \def\ixparam{#1}%
215   \ifx\ixparam\empty%
216     \index{#2}%
217   \else%
218     \index{#1}%
219   \fi}

```

`\emph` Then, we redefine the `\emph` command:

```

220 \renewcommand\emph[1]{\incolor{orange}{\textit{#1}}}

```

`\ybPrintTitlePage` Then, we define the `\ybPrintTitlePage` command:

```

221 \makeatletter
222 \newcommand\ybPrintTitlePage{
223   \ifdefined\yb@authordraft\else
224     \begin{titlepage}
225       \ttfamily
226       \vspace*{\fill}
227       \noindent
228       {\Huge\thetitle}
229       \[1em]
230       by \theauthor{}
231       \[4em]
232       \ifx\thevolume\empty\else%
233         Volume \thevolume{}\
234       \fi
235       \ifx\thedata\empty\else%
236         \thedata{}\
237       \fi
238       \ifx\theversion\empty\else%
239         \theversion{}
240       \fi
241       \vspace*{\fill}

```



```

242 \end{titlepage}
243 \fi
244 }
245 \makeatother

```

`\ybEpigraph` Then, we define the `\ybEpigraph` command to print the epigraph:

```

246 \newcommand\ybEpigraph[3]{
247 \cleardoublepage
248 \vspace*{\fill}
249 \begin{quote}
250 \begin{raggedleft}
251 ‘‘#1’’ \\\[1em]
252 {---} #2 \\\
253 \citetitle{#3}\\
254 \citeyear{#3}\par
255 \end{raggedleft}
256 \end{quote}
257 \vspace*{\fill}}

```

`\ybPrintTOC` Then, we define the `\ybPrintTOC` command to print the table of contents:

```

258 \makeatletter
259 \newcommand\ybPrintTOC{%
260 \ifdefined\yb@authordraft\else%
261 \ifdefined\yb@compact\else\cleardoublepage\fi%
262 {\setstretch{0.7}\tableofcontents}%
263 \fi%
264 }
265 \makeatother

```

`\ybPrintIndex` Then, we configure the `imakeidx` package and define the `\ybPrintIndex` command:

```

266 \RequirePackage{imakeidx}
267 \renewbibmacro*{citeindex}{\indexnames{labelname}{}}
268 \makeindex
269 \indexsetup{othercode={\hyphenpenalty=10000}}
270 \makeatletter
271 \newcommand\ybPrintIndex[1][Index]{%
272 \ifdefined\yb@authordraft\else%
273 \ifdefined\yb@compact\else\cleardoublepage\fi%
274 {%
275 \setstretch{1.0}%
276 \small%
277 \addcontentsline{toc}{chapter}{#1}%
278 \printindex%
279 }%
280 \fi%
281 }
282 \makeatother

```

`\ybQuote` Then, with the help of `wrapfig` and `mdframed`, we define the `\ybQuote` command:

```

283 \RequirePackage{wrapfig}
284 \RequirePackage{mdframed}
285 \RequirePackage{changepage}
286 \strictpagecheck
287 \mdfdefinestyle{quoteodd}{backgroundcolor=black!0,

```

```

288 leftmargin=1em,rightmargin=0em,
289 innerleftmargin=1em,innerrightmargin=0em,
290 innertopmargin=0em,innerbottommargin=0em,
291 skipabove=0em,skipbelow=0em,
292 linewidth=.2em,
293 topline=false,bottomline=false,rightline=false}
294 \mdfdefinestyle{quoteeven}{backgroundcolor=black!0,
295 rightmargin=1em,leftmargin=0em,
296 innerrightmargin=1em,innerleftmargin=0em,
297 innertopmargin=0em,innerbottommargin=0em,
298 skipabove=0em,skipbelow=0em,
299 linewidth=.2em,
300 topline=false,bottomline=false,leftline=false}
301 \makeatletter
302 \newcommand\ybQuote[3]{%
303 \ifthenelse{\isempty{#3}}{\{
304 \ifx\hfuzz#2\hfuzz%
305 \index{#3}%
306 \else%
307 \index{#3, #2}%
308 \fi%
309 }%
310 \ifdim\pagetotal<4\baselineskip\relax%
311 \ClassWarning{yb-book}{ybQuote stays at the top of a page: \detokenize{#1}}%
312 \fi%
313 \ifdim\dimexpr\pagegoal-\pagetotal\relax<8\baselineskip\relax%
314 \ClassWarning{yb-book}{ybQuote stays at the bottom of a page: \detokenize{#1}}%
315 \fi%
316 \def\yb@body{%
317 \raggedright%
318 \ifx\hfuzz#3\hfuzz%
319 #1%
320 \else%
321 ‘#1’\\raggedleft---#2 #3%
322 \fi%
323 }
324 \ifdefined\yb@authordraft%
325 \begin{wrapfigure}{r}{0.4\textwidth}%
326 \begin{mdframed}[style=quoteodd]%
327 \yb@body%
328 \end{mdframed}%
329 \end{wrapfigure}%
330 \else%
331 \begin{wrapfigure}{o}[2em]{0.4\textwidth}%
332 \sffamily\checkoddpage%
333 \ifoddpage%
334 \begin{mdframed}[style=quoteodd]\yb@body\end{mdframed}%
335 \else%
336 \begin{mdframed}[style=quoteeven]\yb@body\end{mdframed}%
337 \fi%
338 \vspace{-1em}
339 \end{wrapfigure}%
340 \fi%
341 }

```

```
342 \makeatother
```

Then, we use and configure `footmisc` as suggested [here](#):

```
343 \RequirePackage{perpage}
344 \PassOptionsToPackage{bottom,perpage,multiple}{footmisc}
345 \RequirePackage{footmisc}
346 \makeatletter
347 \let\yb@oldfootnote\footnote
348 \newcommand\yb@nexttoken\relax
349 \newcommand\yb@isfootnote{%
350 \ifx\footnote\yb@nexttoken\textsuperscript{,}\fi}
351 \renewcommand\footnote[1]{%
352 \yb@oldfootnote{#1}\futurelet\yb@nexttoken\yb@isfootnote}
353 \makeatother
```

`\ybPrintBibliography` Then, we define `\ybPrintBibliography`, to print a list of references:

```
354 \makeatletter
355 \newcommand\ybPrintBibliography[1][Bibliography]{%
356 \AtNextBibliography{\small}%
357 \raggedright%
358 \ifdefined\yb@manuscript%
359 \setlength\bibitemsep{0em}%
360 \newpage%
361 \begin{multicols}{2}%
362 {\setstretch{1.0}\printbibliography}%
363 \end{multicols}%
364 \else%
365 \setlength\bibitemsep{.2em}%
366 \@openrightfalse%
367 \printbibliography[heading=bibintoc,title={#1}]%
368 \ifdefined\yb@compact\@openrighttrue\fi%
369 \fi%
370 }
371 \makeatother
```

`\highlight` Then, we define the `\highlight` command:

```
372 \newcommand\highlight[1]{%
373 \tikz[baseline=(text.base)] {
374 \node[inner sep=0em, outer sep=0em] (text) {%
375 {\ifdefined\yb@colored\color{orange}\fi#1}};
376 \begin{scope}
377 \path[use as bounding box] (text.east) rectangle (text.west);
378 \draw[decorate,
379 decoration={random steps, amplitude=0.05em, segment length=0.3em},
380 line join=round,
381 line cap=round,
382 line width=.08em,
383 draw=gray!80] ($(text.west) + (-0.2em, -.46em)$) rectangle ($(text.east) + (+0.2em, -
384 \end{scope}
385 }%
386 }
```

Then, a few layout configurations at the beginning of the document:

```
387 \makeatletter
```

```

388 \AtBeginDocument{%
389   \raggedbottom%
390   \ifdefined\yb@authordraft%
391     \raggedright%
392   \fi%
393   \setlength\topskip{0em}%
394   \setlength\parindent{0em}%
395   \setlength\fbboxsep{0em}%
396   \setlength\parskip{.5em}%
397   \exhyphenpenalty=10000% to avoid line breaks before and after an em dash
398   \widowpenalty=10000% to have fewer widows
399   \clubpenalty=10000% to have fewer orphans
400   \interfootnotelinepenalty=10000% to format footnotes better
401   \hfuzz=3pt %
402   \tolerance=1000 %
403   \emergencystretch=1em %
404   \hbadness=2000 %
405 }
406 \makeatother

```

Finally, a few meta commands with default values:

```

407 \newcommand*\thetitle{\textbackslash{}\thetitle}
408 \let\thevolume\empty
409 \let\thedate\empty
410 \newcommand*\theversion{\textbackslash{}\theversion}
411 \newcommand*\theauthor{\textbackslash{}\theauthor}
412 \newcommand*\thereviewer{\textbackslash{}\thereviewer}
413
414 \endinput

```

## Change History

v0.1.0		style. . . . .	3
General: Initial version . . . . .	3	v0.6.2	
v0.2.0		<code>\ybPrintBibliography</code> : The	
General: Started using <code>l3build</code> . . .	3	<code>\ybPrintBibliography</code>	
v0.3.0		command has an optional	
General: The <code>pgfopts</code> package is		argument, which is the title of	
now used to parse package		the chapter. . . . .	11
options. . . . .	3	v0.6.6	
v0.4.0		General: Penalties for widows and	
<code>authordraft</code> : The package option		clubs specified. . . . .	11
<code>draft</code> renamed to <code>authordraft</code> . . .	2	v0.7.0	
v0.5.0		General: Added <code>cleveref</code> package	
General: The <code>sparse</code> package		for the <code>\cref</code> command. . . . .	4
option added, to place every		The <code>colored</code> package option	
section on a new page. . . . .	3	added, to enable colors. . . . .	3
v0.5.1		<code>\highlight</code> : The <code>\highlight</code>	
General: Added the usage of		command was added. . . . .	11
<code>inputenc</code> in order to ensure		v0.8.0	
UTF-8 encoding for the sources. . . .	4	General: CMU Concrete is now the	
v0.6.0		default main font; the class	
General: The <code>apa</code> package option		requires XeTeX or LuaTeX and	
added, to enable APA citation		aborts under pdfTeX. . . . .	4

# Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

<b>Symbols</b>		<b>E</b>	<b>\index</b> 216, 218, 305, 307
<b>\@makefnmark</b> . . . . .	151	<b>\emergencystretch</b> . .	403
<b>\@makefnmark</b> . . . . .	148	<b>\emph</b> . . . . .	220
<b>\@openrightfalse</b> . .	366	<b>\endinput</b> . . . . .	37, 414
<b>\@openrighttrue</b> . . .	368	<b>\exhyphenpenalty</b> . .	397
<b>\</b> . . . . .	196, 198, 200, 203, 229, 231, 233, 236, 251, 252, 253, 321	<b>F</b>	
<b>A</b>		<b>\fancyfoot</b> . . . . .	190
<b>\addcontentsline</b> . .	277	<b>\fancyhead</b> . . . . .	164, 165
<b>\addfontfeature</b> . . .	120	<b>\fancyhf</b> . . . . .	163
Amazon . . . . .	1	<b>\fbxsep</b> . . . . .	395
<b>\AtBeginDocument</b> . .	388	<b>\fill</b> . 226, 241, 248, 257	
<b>\AtNextBibliography</b> .	356	<b>\fontsize</b> . . . . .	168
<b>\authordraft</b> . . . . .	1	<b>\footnote</b> . 347, 350, 351	
<b>B</b>		<b>\footrulewidth</b> . . . .	161
<b>\baselineskip</b> . 310, 313		<b>\futurelet</b> . . . . .	352
<b>\bfseries</b> . . . . .	168	<b>G</b>	
<b>\bibitemsep</b> . . . 359, 365		<b>\geometry</b> 45, 46, 52, 55	
<b>\biblatex</b> . . . . .	86	<b>H</b>	
<b>\boolfalse</b> . . . . .		<b>\hb@xt@</b> . . . . .	151
. 99, 100, 109, 110		<b>\hbadness</b> . . . . .	404
<b>C</b>		<b>\headheight</b> . . . . .	162
<b>\checkoddpage</b> . . . .	332	<b>\headrulewidth</b> . . . .	160
<b>\citetitle</b> . 98, 108, 253		<b>\hfuzz</b> . . . . 304, 318, 401	
<b>\citeyear</b> . . . . .	254	<b>\highlight</b> . . . . .	372
<b>\ClassError</b> . . . . .	34	<b>\hss</b> . . . . .	151
<b>\ClassWarning</b> . 311, 314		<b>\Huge</b> . . . . .	228
<b>\cleardoublepage</b> . .		<b>\hyphenpenalty</b> . . . .	269
. . . . 247, 261, 273		<b>I</b>	
<b>\clubpenalty</b> . . . . .	399	<b>\ifciteindex</b> . . 102, 112	
<b>\color</b> . . . . .	171, 375	<b>\ifdefined</b> . . 13, 17,	
<b>\compact</b> . . . . .	1	51, 54, 82, 83, 84,	
<b>\condensed</b> . . . . .	118	90, 124, 133, 134,	
<b>\counterwithout</b> . . .	65	143, 154, 210,	
<b>\crefformat</b> . . . . .	31	223, 260, 261,	
<b>D</b>		272, 273, 324,	
<b>\DeclareCiteCommand</b>		358, 368, 375, 390	
. . . . . 98, 108		<b>\ifdim</b> . . . . .	310, 313
<b>\detokenize</b> . . . 311, 314		<b>\ifoddpage</b> . . . . .	333
<b>\dimexpr</b> . . . . .	313	<b>\ifPDFTeX</b> . . . . .	33
<b>\draw</b> . . . . .	378	<b>\ifthenelse</b> . . . . .	303
		<b>\ifx</b> . . . 199, 202, 205,	
		215, 232, 235,	
		238, 304, 318, 350	
		<b>\incolor</b> . . 209, 213, 220	
		<b>\index</b> 216, 218, 305, 307	
		<b>\indexnames</b> 103, 113, 267	
		<b>\indexsetup</b> . . . . .	269
		<b>\interfootnotelinepenalty</b>	
		. . . . .	400
		<b>\ix</b> . . . . .	212
		<b>\ixparam</b> . . . . .	214, 215
		<b>L</b>	
		<b>\LARGE</b> . . . . .	195
		<b>\LoadClass</b> . . . . .	26
		<b>\lstset</b> . . . . .	121
		<b>M</b>	
		<b>\makeatletter</b> 12, 50,	
		81, 89, 123, 131,	
		147, 153, 209,	
		221, 258, 270,	
		301, 346, 354, 387	
		<b>\makeatother</b> . 25, 58,	
		85, 95, 129, 146,	
		152, 193, 211,	
		245, 265, 282,	
		342, 353, 371, 406	
		<b>\makeindex</b> . . . . .	268
		<b>\maketitle</b> . . . . .	194
		<b>\manuscript</b> . . . . .	1
		<b>\mdfdefinestyle</b> 287, 294	
		<b>\microtype</b> . . . . .	123
		<b>\multicitedelim</b> 106, 116	
		<b>N</b>	
		<b>\newpage</b> . . . . .	133, 360
		<b>\node</b> . 167, 170, 177, 374	
		<b>\noindent</b> . . . . .	151, 227
		<b>P</b>	
		<b>\pagegoal</b> . . . . .	313
		<b>\pageref</b> . . . . .	191
		<b>\pagestyle</b> . . . . .	78, 159
		<b>\pagetotal</b> . . . . .	310, 313
		<b>\par</b> . . . . .	254
		<b>\parindent</b> . . . . .	150, 394
		<b>\parskip</b> . . . . .	396
		<b>\PassOptionsToClass</b>	
		. . . . .	14,
		15, 18, 19, 21, 22	

<code>\PassOptionsToPackage</code>	<code>\setlist</code> . . . . .	72	<b>U</b>
. 28, 70, 76, 86,	<code>\setmainfont</code> . . . . .	40	<code>\usebibmacro</code> . . . . .
91, 93, 125, 127,	<code>\setspace</code> . . . . .	79	. 101, 107, 111, 117
135, 138, 155, 344	<code>\setstretch</code> . . 80, 82,		<code>\usetikzlibrary</code> . . .
<code>\path</code> . . . . .	83, 84, 262, 275, 362		. . . . . 61, 62, 63
<code>\pgfkeys</code> . . . . .	2		<b>V</b>
<code>\printbibliography</code> .	<code>\sffamily</code> . . . . .	332	<code>\vspace</code> . . . 144, 226,
. . . . . 362, 367	<code>\small</code> . . . . 190, 276, 356		241, 248, 257, 338
<code>\printfield</code> . . . 105, 115	<code>\sparse</code> . . . . .	1	<b>W</b>
<code>\printindex</code> . . . . . 278	<code>\strictpagecheck</code> . . 286		<code>\widowpenalty</code> . . . . 398
<code>\ProcessPgfpPackageOptions</code>	<b>T</b>		<b>Y</b>
. . . . . 11	<code>\tableofcontents</code> . . 262		<code>\yb@apa</code> . . . . . 4, 90
<b>R</b>	<code>\textbackslash</code> . . . .		<code>\yb@authordraft</code> . 5,
<code>\raggedbottom</code> . . . . 389	. 407, 410, 411, 412		13, 51, 84, 124,
<code>\raggedleft</code> . . . . . 321	<code>\textbf</code> . . . . . 184, 195		134, 154, 223,
<code>\raggedright</code> . . . . .	<code>\textcolor</code> . . . . . 210		260, 272, 324, 390
. 149, 317, 357, 391	<code>\textcopyright</code> . . . . 179		<code>\yb@body</code> 316, 327, 334, 336
<code>\relax</code> . . . . 310, 313, 348	<code>\textit</code> . . . . . 220		<code>\yb@colored</code> . 8, 210, 375
<code>\renewbibmacro</code> . . . . 267	<code>\textsuperscript</code> . . 350		<code>\yb@compact</code> . . . 6, 82,
<code>\renewcommand</code> . . 141,	<code>\textwidth</code> . . . . 325, 331		143, 261, 273, 368
144, 148, 160,	<code>\the</code> . . . . . 179		<code>\yb@isfootnote</code> 349, 352
161, 194, 220, 351	<code>\theauthor</code> . . . . .		<code>\yb@manuscript</code> . . . .
<code>\RequirePackage</code> . . .	. 179, 197, 230, 411		. 7, 17, 54, 83, 358
. . 1, 27, 29, 30,	<code>\thedate</code> . . . . . 202,		<code>\yb@nexttoken</code> . . . . .
32, 39, 45, 59, 60,	203, 235, 236, 409		. . . . 348, 350, 352
64, 66, 67, 68, 69,	<code>\thepage</code> . . . . . 191		<code>\yb@oldfootnote</code> 347, 352
71, 73, 74, 75, 77,	<code>\thereviewer</code> . . 184, 412		<code>\yb@oldsection</code> . . . .
79, 96, 97, 130,	<code>\thetitle</code> . 195, 228, 407		. . . . 132, 141, 144
136, 139, 156,	<code>\theversion</code> . . . . 205,		<code>\yb@secstart</code> 133, 141, 144
158, 266, 283,	206, 238, 239, 410		<code>\yb@sparse</code> . . . . . 9, 133
284, 285, 343, 345	<code>\thevolume</code> . . . . 199,		<code>\yb@Epigraph</code> . . . . . 246
<code>\rotatebox</code> . . . . . 169	200, 232, 233, 408		<code>\yb@PrintBibliography</code>
<b>S</b>	<code>\tikz</code> . 167, 170, 177, 373		. . . . . 1, 354
<code>\S</code> . . . . . 31	<code>\titlespacing</code> . . . . 140		<code>\yb@PrintIndex</code> . . . 1, 266
<code>\scriptsize</code> . . . . . 178	<code>\tolerance</code> . . . . . 402		<code>\yb@PrintTitlePage</code> 1, 221
<code>\section</code> . . . . . 131	<code>\topskip</code> . . . . . 393		<code>\yb@PrintTOC</code> . . . . 1, 258
<code>\selectfont</code> . . . . . 168	<code>\TPGrid</code> . . . . . 157		<code>\yb@Quote</code> . . . . . 1, 283
<code>\setlength</code> . . . . .	<code>\TPHorizModule</code> . . . 167		<code>\year</code> . . . . . 179
. 162, 359, 365,	<code>\ttfamily</code> . . . . .		
393, 394, 395, 396	. 171, 178, 190, 225		