

Y. B.

## L<sup>A</sup>T<sub>E</sub>X Class yb-book\*

Yegor Bugayenko  
yegor256@gmail.com

2026-05-25, 0.10.0

### 1 Introduction

The class yb-book was devised to assist the author in producing [his books](#) and in publishing them [on Amazon](#). Others are welcome to employ it for their own books. The procedure is straightforward:

```
\documentclass{yb-book}
\renewcommand*\thetitle{New Book About OOP}
\renewcommand*\theauthor{Jeff Lebowski}
\renewcommand*\thevolume{1}
\renewcommand*\theversion{1.0}
\begin{document}
\ybPrintTitlePage
\chapter{First One}
\section{About Something Interesting}
Hello, world!
\end{document}
```

Suggestions for additional options and commands are welcome; nevertheless, the style of the author's books is intentionally as plain as possible, eschewing formatting to the greatest extent practicable. The reasoning is set out [here](#).

### 2 Options

Several class options are available:

**compact** This package option is to be used when the text is required in a more compact form, occupying less vertical space. It proves convenient for works of fiction. The author employs it to render the [Code Ahead](#) book.

**sparse** Under this package option, every section commences on a new page.

---

\*The sources are on GitHub at [yegor256/yb-book](https://github.com/yegor256/yb-book)

- manuscript** Whenever the format is not intended for Amazon printing but for some other purpose (the page size being A4), this option proves convenient. The author likewise employs it whenever the book is to be rendered for printing on paper for review purposes.
- authordraft** This option is appropriate when the document is a draft for reviewers (the page size being A4) and a watermark together with a compact form of the content is desired. The option is used in conjunction with the `\thereviewer{}` command, which may be redefined to embed the name of the reviewer within the watermark. This serves as a deterrent to theft of the book:

```
\documentclass[authordraft]{yb-book}
\renewcommand*\thereviewer{Walter Sobchak}
\begin{document}
Hello, world!
\end{document}
```

### 3 Meta Commands

A number of commands may be redefined within the preamble:

```
\documentclass{yb-book}
\newcommand*\thetitle{My New Book About OOP}
\newcommand*\theauthor{Yegor Bugayenko}
\newcommand*\thevolume{1}
\newcommand*\thedate{24 Feb 2022}
\newcommand*\theversion{1.4}
\newcommand*\thereviewer{Jeff Lebowski}
\begin{document}
... the content goes here ...
\end{document}
```

### 4 Printers

A number of printers are provided—commands that render substantial blocks of text in the expected format:

- \ybPrintTitlePage** Prints the first page of a book. At minimum, `\thetitle` and `\theauthor` must be defined:

```
\documentclass{yb-book}
\renewcommand*\thetitle{My New Book}
\renewcommand*\theauthor{Yegor Bugayenko}
\begin{document}
\ybPrintTitlePage
.. the rest of the book goes here
\end{document}
```

- \ybPrintTOC** Prints the table of contents.

- \ybQuote** Prints a side quote:

```
\documentclass{yb-book}
```

```

\begin{document}
Hello, world!
\ybQuote{Never tell the truth to people who
are not worthy of it}{Mark Twain}{}
\end{document}

```

A warning is emitted to the log whenever the quotation falls very close to the top or the bottom of a page, since the underlying `wrapfig` environment behaves poorly in such positions.

`\ybPrintBibliography` Prints the list of bib references.

`\ybPrintIndex` Prints index with an optional name of the section (instead of “Index”):

```

\documentclass{yb-book}
\begin{document}
Hello, world!
\ybPrintIndex[Recommended Books]
\end{document}

```

## 5 Implementation

First, we parse package options:

```

1 \RequirePackage{pgfopts}
2 \pgfkeys{
3   /yb/.cd,
4   apa/.store in=\yb@apa,
5   authordraft/.store in=\yb@authordraft,
6   compact/.store in=\yb@compact,
7   manuscript/.store in=\yb@manuscript,
8   colored/.store in=\yb@colored,
9   sparse/.store in=\yb@sparse,
10 }
11 \ProcessPgfPackageOptions{/yb}

```

Then, depending on the options like `authordraft` and `manuscript`, we preset options of the class `book` and then load it:

```

12 \makeatletter
13 \ifdefined\yb@authordraft
14   \PassOptionsToClass{11pt}{book}
15   \PassOptionsToClass{oneside}{book}
16 \else
17   \ifdefined\yb@manuscript
18     \PassOptionsToClass{12pt}{book}
19     \PassOptionsToClass{oneside}{book}
20   \else
21     \PassOptionsToClass{11pt}{book}
22     \PassOptionsToClass{twoside}{book}
23   \fi
24 \fi
25 \makeatother
26 \LoadClass{book}

```

Then, we load `href-ul` to underline links correctly:

```

27 \RequirePackage{href-ul}

```

Then, we load [cleveref](#) for the `\cref` command:

```
28 \PassOptionsToPackage{capitalize}{cleveref}
29 \RequirePackage{amsmath}
30 \RequirePackage{cleveref}
31 \crefformat{section}{\S#2#1#3}
```

The class does not change the main font; the default Computer Modern Roman is used. Document authors are free to select a different font in their own preamble.

`geometry` Then, using `geometry`, we set up page layout:

```
32 \RequirePackage{geometry}
33 \geometry{
34   paperwidth=6in, paperheight=9in,
35   bindingoffset=0.25in,
36   left=0.75in, right=0.75in, top=0.75in, bottom=1.25in}
37 \makeatletter
38 \ifdefined\yb@authordraft
39   \geometry{a4paper, margin=1in, left=1.5in}
40 \else
41   \ifdefined\yb@manuscript
42     \geometry{a4paper, margin=1.2in}
43   \fi
44 \fi
45 \makeatother
```

Then, we load [anyfontsize](#) to enable all sizes of fonts:

```
46 \RequirePackage{anyfontsize}
```

Then, we load [tikz](#) for graphics:

```
47 \RequirePackage{tikz}
48 \usetikzlibrary{positioning}
49 \usetikzlibrary{shapes}
50 \usetikzlibrary{fit}
```

Then, we load [chngcntr](#) for something else:

```
51 \RequirePackage{chngcntr}
52 \counterwithout{footnote}{chapter}
```

Then, we load [lastpage](#) to enable rendering of the last page number:

```
53 \RequirePackage{lastpage}
```

Then, we load [paralist](#) for inline enumeration:

```
54 \RequirePackage{paralist}
```

Then, we load [xcolor](#) for colors:

```
55 \RequirePackage{xcolor}
```

Then, we load [graphicx](#) to enable graphic files inclusion:

```
56 \RequirePackage{graphicx}
```

Then, we load [enumitem](#) for inline enumeration:

```
57 \PassOptionsToPackage{inline}{enumitem}
58 \RequirePackage{enumitem}
59 \setlist{nosep}
```

Then, we load [float](#) for floating figures:

```
60 \RequirePackage{float}
```

Then, we load [xifthen](#) and [xifthen](#) for if-then-else:

```
61 \RequirePackage{xifp}
62 \RequirePackage{xifthen}
```

Then, we load [csquotes](#) for better rendering:

```
63 \PassOptionsToPackage{autostyle=try}{csquotes}
64 \RequirePackage{csquotes}
```

`\pagestyle` Then, we set the layout of a page to plain:

```
65 \pagestyle{plain}
```

`setspace` Then, using `setspace` package we set the spacing between lines in the text, depending on the package options:

```
66 \RequirePackage{setspace}
67 \setstretch{1.2}
68 \makeatletter
69 \ifdefined\yb@compact\setstretch{1.0}\fi
70 \ifdefined\yb@manuscript\setstretch{1.1}\fi
71 \ifdefined\yb@authordraft\setstretch{1.4}\fi
72 \makeatother
```

`biblatex` Then, we configure `biblatex` for citation management:

```
73 \PassOptionsToPackage{indexing=cite,
74 natbib=true,maxnames=2,minnames=1,doi=true,
75 url=false,isbn=false}{biblatex}
76 \makeatletter
77 \ifdefined\yb@apa
78 \PassOptionsToPackage{style=authoryear}{biblatex}
79 \else
80 \PassOptionsToPackage{style=numeric}{biblatex}
81 \fi
82 \makeatother
83 \RequirePackage{doi}
84 \RequirePackage{biblatex}
85 \DeclareCiteCommand{\citetitle}
86 {\boolfalse{citetracker}%
87 \boolfalse{pagetracker}%
88 \usebibmacro{prenote}}
89 {\ifciteindex
90 {\indexnames{labelname}}
91 {}}%
92 \printfield[citetitle]{labeltitle}}
93 {\multicitedelim}
94 {\usebibmacro{postnote}}
95 \DeclareCiteCommand*\citetitle
96 {\boolfalse{citetracker}%
97 \boolfalse{pagetracker}%
98 \usebibmacro{prenote}}
99 {\ifciteindex
100 {\indexnames{labelname}}
101 {}}%
102 \printfield[citetitle]{title}}
103 {\multicitedelim}
104 {\usebibmacro{postnote}}
```

condensed Then, we define condensed environment for snippets:

```
105 \newenvironment{condensed}
106   {\begingroup%
107     \addfontfeature{LetterSpace=-15}%
108     \lstset{columns=fixed,basewidth=0.45em}}
109   {\endgroup}
```

microtype Then, we include microtype for better rendering:

```
110 \makeatletter
111 \ifdefined\yb@authordraft
112   \PassOptionsToPackage{nopatch=footnote}{microtype}
113 \else
114   \PassOptionsToPackage{nopatch=footnote,protrusion=true}{microtype}
115 \fi
116 \makeatother
117 \RequirePackage{microtype}
```

\section Then, we redefine the \section command:

```
118 \makeatletter
119 \let\yb@oldsection\section
120 \def\yb@secstart{\ifdefined\yb@sparse\newpage\fi}
121 \ifdefined\yb@authordraft
122   \PassOptionsToPackage{medium}{titlesec}
123   \RequirePackage{titlesec}
124 \else
125   \PassOptionsToPackage{raggedright}{titlesec}
126   \RequirePackage{titlesec}
127   \titlespacing{\section}{0em}{2em}{1em}
128   \renewcommand\section{\yb@secstart\yb@oldsection}
129 \fi
130 \ifdefined\yb@compact
131   \renewcommand\section{\yb@secstart\vspace{2em}\yb@oldsection}
132 \fi
133 \makeatother
```

Then, we do small tweaking:

```
134 \makeatletter
135 \renewcommand\@makefnmark[1]{%
136   \raggedright%
137   \parindent=1em%
138   \noindent\hb@xt@1.8em{\hss\@makefnmark}#1}
139 \makeatother
```

Then, if it's an authordraft, we put a watermark comment:

```
140 \makeatletter
141 \ifdefined\yb@authordraft
142   \PassOptionsToPackage{absolute}{textpos}
143   \RequirePackage{textpos}
144   \TPGrid{16}{16}
145   \RequirePackage{fancyhdr}
146   \pagestyle{fancy}
147   \renewcommand\headrulewidth{0em}
148   \renewcommand\footrulewidth{0em}
149   \setlength{\headheight}{3em}
```

```

150 \fancyhf{}
151 \fancyhead[L,C,LO,CO]{}
152 \fancyhead[R,RO]{
153   \begin{textblock}{16}[0.5,0.5](8,8)%
154     \tikz \node[minimum width=16\TPHorizModule] {%
155       \fontsize{64}{64}\selectfont\bfseries%
156       \rotatebox{45}{
157         \tikz \node
158           [fill=gray!6, font=\ttfamily\color{white}]
159           {it is a draft};%
160       }%
161     };%
162   \end{textblock}%
163   \begin{textblock}{4}(11.5,1)%
164     \tikz \node [color=gray, rotate=270,
165       font=\ttfamily\scriptsize, text width=24em] at (0,0) {%
166       Copyright \textcopyright{} \the\year{} by \theauthor{}.
167       All rights reserved. No part of the contents of
168       this book may be reproduced or transmitted in any
169       form or by any means without the written permission
170       of the publisher. This particular manuscript is
171       printed for \textbf{\thereviewer{}} and may be used only
172       for one-time review. The manuscript has to be destroyed
173       after the review.%
174     };
175   \end{textblock}
176 }
177 \fancyfoot[C,CO,C]{\small\ttfamily%
178   page \thepage{} of \pageref{LastPage}}
179 \fi
180 \makeatother

```

`\maketitle` Then, we redefine the `\maketitle` command:

```

181 \renewcommand\maketitle{
182   {\LARGE\textbf{\thetitle}}
183   \[1em]
184   by \theauthor{}
185   \[4em]
186   \ifx\thevolume\empty\else%
187     Volume \thevolume{}\
188   \fi
189   \ifx\thedate\empty\else%
190     Rendered on \thedate{}\
191   \fi
192   \ifx\theversion\empty\else%
193     Ver. \theversion{}
194   \fi
195 }

```

`\incolor` Then, we define the `\incolor` command:

```

196 \makeatletter
197 \newcommand\incolor[2]{\ifdefined\yb@colored\textcolor{#1}{#2}\else#2\fi}
198 \makeatother

```

\ix Then, we define the \ix command:

```
199 \newcommand\ix[2] []{%
200   \incolor{brown}{#2}%
201   \def\ixparam{#1}%
202   \ifx\ixparam\empty%
203     \index{#2}%
204   \else%
205     \index{#1}%
206   \fi}
```

\emph Then, we redefine the \emph command:

```
207 \renewcommand\emph[1]{\incolor{orange}{\textit{#1}}}
```

\ybPrintTitlePage Then, we define the \ybPrintTitlePage command:

```
208 \makeatletter
209 \newcommand\ybPrintTitlePage{
210   \ifdefined\yb@authordraft\else
211     \begin{titlepage}
212       \ttfamily
213       \vspace*{\fill}
214       \noindent
215       {\Huge\thetitle}
216       \\[1em]
217       by \theauthor{}
218       \\[4em]
219       \ifx\thevolume\empty\else%
220         Volume \thevolume{}\
221       \fi
222       \ifx\thedate\empty\else%
223         \thedate{}\
224       \fi
225       \ifx\theversion\empty\else%
226         \theversion{}
227       \fi
228       \vspace*{\fill}
229     \end{titlepage}
230   \fi
231 }
232 \makeatother
```

\ybEpigraph Then, we define the \ybEpigraph command to print the epigraph:

```
233 \newcommand\ybEpigraph[3]{
234   \cleardoublepage
235   \vspace*{\fill}
236   \begin{quote}
237     \begin{raggedleft}
238       ‘#1’ \\[1em]
239       {---} #2 \
240       \citetitle{#3}\
241       \citeyear{#3}\par
242     \end{raggedleft}
243   \end{quote}
244   \vspace*{\fill}}
```

`\ybPrintTOC` Then, we define the `\ybPrintTOC` command to print the table of contents:

```
245 \makeatletter
246 \newcommand\ybPrintTOC{%
247   \ifdefined\yb@authordraft\else%
248     \ifdefined\yb@compact\else\cleardoublepage\fi%
249     {\setstretch{0.7}\tableofcontents}%
250   \fi%
251 }
252 \makeatother
```

`\ybPrintIndex` Then, we configure the `imakeidx` package and define the `\ybPrintIndex` command:

```
253 \RequirePackage{imakeidx}
254 \renewbibmacro*{citeindex}{\indexnames{labelname}{}}
255 \makeindex
256 \indexsetup{othercode={\hyphenpenalty=10000}}
257 \makeatletter
258 \newcommand\ybPrintIndex[1][Index]{%
259   \ifdefined\yb@authordraft\else%
260     \ifdefined\yb@compact\else\cleardoublepage\fi%
261   {%
262     \setstretch{1.0}%
263     \small%
264     \addcontentsline{toc}{chapter}{#1}%
265     \printindex%
266   }%
267   \fi%
268 }
269 \makeatother
```

`\ybQuote` Then, with the help of `wrapfig` and `mdframed`, we define the `\ybQuote` command:

```
270 \RequirePackage{wrapfig}
271 \RequirePackage{mdframed}
272 \RequirePackage{changepage}
273 \strictpagecheck
274 \mdfdefinestyle{quoteodd}{backgroundcolor=black!0,
275   leftmargin=1em,rightmargin=0em,
276   innerleftmargin=1em,innerrightmargin=0em,
277   innertopmargin=0em,innerbottommargin=0em,
278   skipabove=0em,skipbelow=0em,
279   linewidth=.2em,
280   topline=false,bottomline=false,rightline=false}
281 \mdfdefinestyle{quoteeven}{backgroundcolor=black!0,
282   rightmargin=1em,leftmargin=0em,
283   innerrightmargin=1em,innerleftmargin=0em,
284   innertopmargin=0em,innerbottommargin=0em,
285   skipabove=0em,skipbelow=0em,
286   linewidth=.2em,
287   topline=false,bottomline=false,leftline=false}
288 \makeatletter
289 \newcommand\ybQuote[3]{%
290   \ifthenelse{\isempty{#3}}{\}{
291     \ifx\hfuzz#2\hfuzz%
292       \index{#3}%
293     \else%
```

```

294     \index{#3, #2}%
295     \fi%
296 }%
297 \ifdim\pagetotal<4\baselineskip\relax%
298   \ClassWarning{yb-book}{ybQuote stays at the top of a page: \detokenize{#1}}%
299 \fi%
300 \ifdim\dimexpr\pagegoal-\pagetotal\relax<8\baselineskip\relax%
301   \ClassWarning{yb-book}{ybQuote stays at the bottom of a page: \detokenize{#1}}%
302 \fi%
303 \def\yb@body{%
304   \raggedright%
305   \ifx\hfuzz#3\hfuzz%
306     #1%
307   \else%
308     ‘#1’\raggedleft---#2 #3%
309   \fi%
310 }
311 \ifdefined\yb@authordraft%
312   \begin{wrapfigure}{r}{0.4\textwidth}%
313     \begin{mdframed}[style=quoteodd]%
314       \yb@body%
315     \end{mdframed}%
316   \end{wrapfigure}%
317 \else%
318   \begin{wrapfigure}{o}[2em]{0.4\textwidth}%
319     \sffamily\checkoddpage%
320     \ifoddpage%
321       \begin{mdframed}[style=quoteodd]\yb@body\end{mdframed}%
322     \else%
323       \begin{mdframed}[style=quoteeven]\yb@body\end{mdframed}%
324     \fi%
325     \vspace{-1em}
326   \end{wrapfigure}%
327 \fi%
328 }
329 \makeatother

```

Then, we use and configure footmisc as suggested [here](#):

```

330 \RequirePackage{perpage}
331 \PassOptionsToPackage{bottom,perpage,multiple}{footmisc}
332 \RequirePackage{footmisc}
333 \makeatletter
334 \let\yb@oldfootnote\footnote
335 \newcommand\yb@nexttoken\relax
336 \newcommand\yb@isfootnote{%
337   \ifx\footnote\yb@nexttoken\textsuperscript{,}\fi}
338 \renewcommand\footnote[1]{%
339   \yb@oldfootnote{#1}\futurelet\yb@nexttoken\yb@isfootnote}
340 \makeatother

```

\ybPrintBibliography Then, we define \ybPrintBibliography, to print a list of references:

```

341 \makeatletter
342 \newcommand\ybPrintBibliography[1][Bibliography]{%
343   \AtNextBibliography{\small}%

```

```

344 \raggedright%
345 \ifdefined\yb@manuscript%
346   \setlength\bibitemsep{0em}%
347   \newpage%
348   \begin{multicols}{2}%
349     {\setstretch{1.0}\printbibliography}%
350   \end{multicols}%
351 \else%
352   \setlength\bibitemsep{.2em}%
353   \@openrightfalse%
354   \printbibliography[heading=bibintoc,title={#1}]%
355   \ifdefined\yb@compact\@openrighttrue\fi%
356 \fi%
357 }
358 \makeatother

```

`\highlight` Then, we define the `\highlight` command:

```

359 \newcommand\highlight[1]{%
360   \tikz[baseline=(text.base)] {
361     \node[inner sep=0em, outer sep=0em] (text) {%
362       {\ifdefined\yb@colored\color{orange}\fi#1}};
363     \begin{scope}
364       \path[use as bounding box] (text.east) rectangle (text.west);
365       \draw[decorate,
366         decoration={random steps, amplitude=0.05em, segment length=0.3em},
367         line join=round,
368         line cap=round,
369         line width=.08em,
370         draw=gray!80] ($(text.west) + (-0.2em, -.46em)$) rectangle ($(text.east) + (+0.2em, -
371       \end{scope}
372   }%
373 }

```

Then, a few layout configurations at the beginning of the document:

```

374 \makeatletter
375 \AtBeginDocument{%
376   \raggedbottom%
377   \ifdefined\yb@authordraft%
378     \raggedright%
379   \fi%
380   \setlength\topskip{0em}%
381   \setlength\parindent{0em}%
382   \setlength\fbboxsep{0em}%
383   \setlength\parskip{.5em}%
384   \exhyphenpenalty=10000% to avoid line breaks before and after an em dash
385   \widowpenalty=10000% to have fewer widows
386   \clubpenalty=10000% to have fewer orphans
387   \interfootnotelinepenalty=10000% to format footnotes better
388   \hfuzz=3pt %
389   \tolerance=1000 %
390   \emergencystretch=1em %
391   \hbadness=2000 %
392 }
393 \makeatother

```

Finally, a few meta commands with default values:

```
394 \newcommand*\thetitle{\textbackslash{}thetitle}
395 \let\thevolume\empty
396 \let\thedate\empty
397 \newcommand*\theversion{\textbackslash{}theversion}
398 \newcommand*\theauthor{\textbackslash{}theauthor}
399 \newcommand*\thereviewer{\textbackslash{}thereviewer}
400
401 \endinput
```

## Change History

v0.1.0		style. . . . .	3
General: Initial version . . . . .	3	v0.6.2	
v0.2.0		<code>\ybPrintBibliography</code> : The	
General: Started using <code>l3build</code> . . .	3	<code>\ybPrintBibliography</code>	
v0.3.0		command has an optional	
General: The <code>pgfopts</code> package is		argument, which is the title of	
now used to parse package		the chapter. . . . .	10
options. . . . .	3	v0.6.6	
v0.4.0		General: Penalties for widows and	
<code>authordraft</code> : The package option		clubs specified. . . . .	11
<code>draft</code> renamed to <code>authordraft</code>	2	v0.7.0	
v0.5.0		General: Added <code>cleveref</code> package	
General: The <code>sparse</code> package		for the <code>\cref</code> command. . . . .	4
option added, to place every		The <code>colored</code> package option	
section on a new page. . . . .	3	added, to enable colors. . . . .	3
v0.5.1		<code>\highlight</code> : The <code>\highlight</code>	
General: Added the usage of		command was added. . . . .	11
<code>inputenc</code> in order to ensure		v0.8.1	
UTF-8 encoding for the sources. . . . .	4	General: Removed the CMU	
v0.6.0		Concrete font setup; the class	
General: The <code>apa</code> package option		no longer changes the main font	
added, to enable APA citation		and works under any engine. . . . .	4

# Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

<b>Symbols</b>	<code>\emph</code> . . . . . <a href="#">207</a>	<code>\interfootnotelinepenalty</code>
<code>\@makefnmark</code> . . . . . <a href="#">138</a>	<code>\endinput</code> . . . . . <a href="#">401</a>	. . . . . <a href="#">387</a>
<code>\@makefn<del>text</del></code> . . . . . <a href="#">135</a>	<code>\exhyphenpenalty</code> . . <a href="#">384</a>	<code>\ix</code> . . . . . <a href="#">199</a>
<code>\@openrightfalse</code> . . <a href="#">353</a>		<code>\ixparam</code> . . . . . <a href="#">201, 202</a>
<code>\@openrighttrue</code> . . . <a href="#">355</a>	<b>F</b>	
<code>\@</code> . . . . . <a href="#">183, 185,</a>	<code>\fancyfoot</code> . . . . . <a href="#">177</a>	<b>L</b>
<a href="#">187, 190, 216,</a>	<code>\fancyhead</code> . . . . . <a href="#">151, 152</a>	<code>\LARGE</code> . . . . . <a href="#">182</a>
<a href="#">218, 220, 223,</a>	<code>\fancyhf</code> . . . . . <a href="#">150</a>	<code>\LoadClass</code> . . . . . <a href="#">26</a>
<a href="#">238, 239, 240, 308</a>	<code>\fboxsep</code> . . . . . <a href="#">382</a>	<code>\lstset</code> . . . . . <a href="#">108</a>
<b>A</b>	<code>\fill</code> . <a href="#">213, 228, 235, 244</a>	
<code>\addcontentsline</code> . . <a href="#">264</a>	<code>\fontsize</code> . . . . . <a href="#">155</a>	<b>M</b>
<code>\addfontfeature</code> . . . <a href="#">107</a>	<code>\footnote</code> . <a href="#">334, 337, 338</a>	<code>\makeatletter</code> <a href="#">12, 37,</a>
Amazon . . . . . <a href="#">1</a>	<code>\footrulewidth</code> . . . . <a href="#">148</a>	<a href="#">68, 76, 110, 118,</a>
<code>\AtBeginDocument</code> . . <a href="#">375</a>	<code>\futurelet</code> . . . . . <a href="#">339</a>	<a href="#">134, 140, 196,</a>
<code>\AtNextBibliography</code> <a href="#">343</a>		<a href="#">208, 245, 257,</a>
<code>\authordraft</code> . . . . . <a href="#">1</a>	<b>G</b>	<a href="#">288, 333, 341, 374</a>
	<code>\geometry</code> <a href="#">32, 33, 39, 42</a>	<code>\makeatother</code> . <a href="#">25, 45,</a>
<b>B</b>	<b>H</b>	<a href="#">72, 82, 116, 133,</a>
<code>\baselineskip</code> . <a href="#">297, 300</a>	<code>\hb@xt@</code> . . . . . <a href="#">138</a>	<a href="#">139, 180, 198,</a>
<code>\bfseries</code> . . . . . <a href="#">155</a>	<code>\hbadness</code> . . . . . <a href="#">391</a>	<a href="#">232, 252, 269,</a>
<code>\bibitemsep</code> . . . <a href="#">346, 352</a>	<code>\headheight</code> . . . . . <a href="#">149</a>	<a href="#">329, 340, 358, 393</a>
<code>\biblatex</code> . . . . . <a href="#">73</a>	<code>\headrulewidth</code> . . . . <a href="#">147</a>	<code>\makeindex</code> . . . . . <a href="#">255</a>
<code>\boolfalse</code> <a href="#">86, 87, 96, 97</a>	<code>\hfuzz</code> . . . . . <a href="#">291, 305, 388</a>	<code>\maketitle</code> . . . . . <a href="#">181</a>
<b>C</b>	<code>\highlight</code> . . . . . <a href="#">359</a>	<code>\manuscript</code> . . . . . <a href="#">1</a>
<code>\checkoddpage</code> . . . . . <a href="#">319</a>	<code>\hss</code> . . . . . <a href="#">138</a>	<code>\mdfdefinestyle</code> <a href="#">274, 281</a>
<code>\citetitle</code> . . <a href="#">85, 95, 240</a>	<code>\Huge</code> . . . . . <a href="#">215</a>	<code>\microtype</code> . . . . . <a href="#">110</a>
<code>\citeyear</code> . . . . . <a href="#">241</a>	<code>\hyphenpenalty</code> . . . . <a href="#">256</a>	<code>\multicitedelim</code> <a href="#">93, 103</a>
<code>\ClassWarning</code> . <a href="#">298, 301</a>	<b>I</b>	<b>N</b>
<code>\cleardoublepage</code> . .	<code>\ifciteindex</code> . . . . . <a href="#">89, 99</a>	<code>\newpage</code> . . . . . <a href="#">120, 347</a>
. . . . . <a href="#">234, 248, 260</a>	<code>\ifdefined</code> . . . <a href="#">13, 17,</a>	<code>\node</code> . <a href="#">154, 157, 164, 361</a>
<code>\clubpenalty</code> . . . . . <a href="#">386</a>	<a href="#">38, 41, 69, 70, 71,</a>	<code>\noindent</code> . . . . . <a href="#">138, 214</a>
<code>\color</code> . . . . . <a href="#">158, 362</a>	<a href="#">77, 111, 120, 121,</a>	<b>P</b>
<code>\compact</code> . . . . . <a href="#">1</a>	<a href="#">130, 141, 197,</a>	<code>\pagegoal</code> . . . . . <a href="#">300</a>
<code>\condensed</code> . . . . . <a href="#">105</a>	<a href="#">210, 247, 248,</a>	<code>\pageref</code> . . . . . <a href="#">178</a>
<code>\counterwithout</code> . . . <a href="#">52</a>	<a href="#">259, 260, 311,</a>	<code>\pagestyle</code> . . . . . <a href="#">65, 146</a>
<code>\crefformat</code> . . . . . <a href="#">31</a>	<a href="#">345, 355, 362, 377</a>	<code>\pagetotal</code> . . . . . <a href="#">297, 300</a>
<b>D</b>	<code>\ifdim</code> . . . . . <a href="#">297, 300</a>	<code>\par</code> . . . . . <a href="#">241</a>
<code>\DeclareCiteCommand</code>	<code>\ifoddpage</code> . . . . . <a href="#">320</a>	<code>\parindent</code> . . . . . <a href="#">137, 381</a>
. . . . . <a href="#">85, 95</a>	<code>\ifthenelse</code> . . . . . <a href="#">290</a>	<code>\parskip</code> . . . . . <a href="#">383</a>
<code>\detokenize</code> . . . <a href="#">298, 301</a>	<code>\ifx</code> . . . <a href="#">186, 189, 192,</a>	<code>\PassOptionsToClass</code>
<code>\dimexpr</code> . . . . . <a href="#">300</a>	<a href="#">202, 219, 222,</a>	. . . . . <a href="#">14,</a>
<code>\draw</code> . . . . . <a href="#">365</a>	<a href="#">225, 291, 305, 337</a>	<a href="#">15, 18, 19, 21, 22</a>
<b>E</b>	<code>\incolor</code> . . <a href="#">196, 200, 207</a>	<code>\PassOptionsToPackage</code>
<code>\emergencystretch</code> . . <a href="#">390</a>	<code>\index</code> <a href="#">203, 205, 292, 294</a>	. <a href="#">28, 57, 63, 73,</a>
	<code>\indexnames</code> <a href="#">90, 100, 254</a>	<a href="#">78, 80, 112, 114,</a>
	<code>\indexsetup</code> . . . . . <a href="#">256</a>	<a href="#">122, 125, 142, 331</a>

<code>\path</code> .....	364	<code>\setstretch</code> ..	67, 69,	<code>\usetikzlibrary</code> ...	
<code>\pgfkeys</code> .....	2		70, 71, 249, 262, 349	.....	48, 49, 50
<code>\printbibliography</code> .		<code>\sffamily</code> .....	319		
.....	349, 354	<code>\small</code> ....	177, 263, 343		
<code>\printfield</code> ....	92, 102	<code>\sparse</code> .....	<u>1</u>	<b>V</b>	
<code>\printindex</code> .....	265	<code>\strictpagecheck</code> ..	273	<code>\vspace</code> ...	131, 213,
<code>\ProcessPgfPackageOptions</code>				.....	228, 235, 244, 325
.....	11				
		<b>T</b>			
<b>R</b>		<code>\tableofcontents</code> ..	249	<b>W</b>	
<code>\raggedbottom</code> .....	376	<code>\textbackslash</code> ....		<code>\widowpenalty</code> .....	385
<code>\raggedleft</code> .....	308	.....	394, 397, 398, 399		
<code>\raggedright</code> .....		<code>\textbf</code> .....	171, 182	<b>Y</b>	
.....	136, 304, 344, 378	<code>\textcolor</code> .....	197	<code>\yb@apa</code> .....	4, 77
<code>\relax</code> ....	297, 300, 335	<code>\textcopyright</code> ....	166	<code>\yb@authordraft</code> .	5,
<code>\renewbibmacro</code> ....	254	<code>\textit</code> .....	207	.....	13, 38, 71, 111,
<code>\renewcommand</code> ..	128,	<code>\textsuperscript</code> ..	337	.....	121, 141, 210,
.....	131, 135, 147,	<code>\textwidth</code> ....	312, 318	.....	247, 259, 311, 377
.....	148, 181, 207, 338	<code>\the</code> .....	166	<code>\yb@body</code> 303, 314, 321, 323	
<code>\RequirePackage</code> 1, 27,		<code>\theauthor</code> .....		.....	8, 197, 362
.....	29, 30, 32, 46, 47,	<code>\thedate</code> .....	189,	<code>\yb@compact</code> ...	6, 69,
.....	51, 53, 54, 55, 56,	.....	190, 222, 223, 396	.....	130, 248, 260, 355
.....	58, 60, 61, 62, 64,	<code>\thepage</code> .....	178	<code>\yb@isfootnote</code> 336, 339	
.....	66, 83, 84, 117,	<code>\thereviewer</code> ..	171, 399	<code>\yb@manuscript</code> ....	
.....	123, 126, 143,	<code>\thetitle</code> .	182, 215, 394	.....	7, 17, 41, 70, 345
.....	145, 253, 270,	<code>\theversion</code> ....	192,	<code>\yb@nexttoken</code> .....	
.....	271, 272, 330, 332	.....	193, 225, 226, 397	.....	335, 337, 339
<code>\rotatebox</code> .....	156	<code>\thevolume</code> .....	186,	<code>\yb@oldfootnote</code> 334, 339	
		.....	187, 219, 220, 395	<code>\yb@oldsection</code> ....	
<b>S</b>		<code>\tikz</code> .	154, 157, 164, 360	.....	119, 128, 131
<code>\S</code> .....	31	<code>\titlespacing</code> .....	127	<code>\yb@secstart</code> 120, 128, 131	
<code>\scriptsize</code> .....	165	<code>\tolerance</code> .....	389	<code>\yb@sparse</code> .....	9, 120
<code>\section</code> .....	<u>118</u>	<code>\topskip</code> .....	380	.....	233
<code>\selectfont</code> .....	155	<code>\TPGrid</code> .....	144	<code>\ybEpigraph</code> .....	<u>233</u>
<code>\setlength</code> .....		<code>\TPHorizModule</code> ....	154	<code>\ybPrintBibliography</code>	
.....	149, 346, 352,	<code>\ttfamily</code> .....		.....	<u>1</u> , <u>341</u>
.....	380, 381, 382, 383	.....	158, 165, 177, 212	<code>\ybPrintIndex</code> ...	<u>1</u> , <u>253</u>
<code>\setlist</code> .....	59	<b>U</b>		<code>\ybPrintTitlePage</code> <u>1</u> , <u>208</u>	
<code>\setspace</code> .....	66	<code>\usebibmacro</code> .....		.....	<u>1</u> , <u>245</u>
		.....	88, 94, 98, 104	<code>\ybPrintTOC</code> .....	<u>1</u> , <u>270</u>
				.....	166
				<code>\ybQuote</code> .....	<u>1</u> , <u>270</u>
				<code>\year</code> .....	166