

Descriptors, Decorators, Metaclasses

Python's "Black Magic" ...(?)

Descriptors

- the key infrastructure of Python's OOP
- attribute access (get, set, delete) ->
 - search class/superclasses dicts for name
 - if suitable **descriptor** found, delegate
- all descriptors have method `__get__`
- if also has `__set__`, **data descriptor** (aka **override descriptor**)
 - class overrides instance
 - otherwise, non-data/non-override desc.

Descriptor mechanics (r)

```
x = C(); print x.foo
```

==>

```
if hasattr(C, 'foo'):
    d = C.foo; D = d.__class__
    if hasattr(D, '__get__') \
        and (hasattr(D, '__set__')
              or 'foo' not in x.__dict__):
        return D.__get__(d, x, C)
return x.__dict__['foo']
```

Descriptor mechanics (w)

```
x = C(); x.foo = 23
```

==>

```
if hasattr(C, 'foo'):
    d = C.foo; D = d.__class__
    if hasattr(D, '__set__'):
        D.__set__(d, x, 23)
    return
x.__dict__['foo'] = 23
```

Functions 'r descriptors

```
def adder(x, y): return x + y
add23 = adder.__get__(23)
add42 = adder.__get__(42)

print add23(100), add42(1000)
123 1042
```

property built-in type

```
property(fget=None, fset=None,  
        fdel=None, doc=None)
```

```
# signatures (doc is just a string)  
# fget(obj) -> value  
# fset(obj, value)  
# fdel(obj)  
class Foo(object):  
    def getBar(self): return 23  
    def setBar(self, val): pass  
    def delBar(self): pass  
    bar = property(getBar, setBar, delBar,  
                  "barbarian rhubarb baritone")
```

property & inheritance

...a tricky issue w/property & inheritance:

```
class Base(object):
    def getFoo(self): return 23
    foo = property(getFoo)
```

```
class Derived(object):
    def getFoo(self): return 42
```

```
d = Derived()
print d.foo
23    # ...???
```

The extra-indirection fix

```
class Base(object):
    def getFoo(self): return 23
    def _fooget(self): return self.getFoo()
    foo = property(_fooget)

class Derived(object):
    def getFoo(self): return 42

d = Derived()
print d.foo
```

Custom descriptors

```
class DefaultAlias(object):
    " overridable aliased attribute "
    def __init__(self, nm): self.nm = nm
    def __get__(self, obj, cls):
        if inst is None: return self
        else: return getattr(obj, self.nm)

class Alias(DefaultAlias):
    " unconditional aliased attribute "
    def __set__(self, obj, value):
        setattr(obj, self.nm, value)
    def __delete__(self, obj):
        delattr(obj, self.nm)
```

Just-in-Time computation

```
class Jit(object):
    def __init__(self, meth, name=None):
        if name is None: name = meth.__name__
        self.meth = meth
        self.name = name
    def __get__(self, obj, cls):
        if obj is None: return self
        result = self.meth(obj)
        setattr(obj, self.name, result)
        return result
```

NB: same inheritance issues as property!

Decorators

- A minor syntax tweak, but...
 - syntax matters, often in unexpected ways

```
@foo  
def bar(...
```

...

==>

```
def bar(...
```

...

```
bar = foo(bar)
```

Decorators without args

```
class X(object):  
    @staticmethod  
    def hello(): print "hello world"
```

==>

```
class X(object):  
    def hello(): print "hello world"  
    hello = staticmethod(hello)
```

Decorators with args

```
def withlock(L):
    def lock_around(f):
        def locked(*a, **k):
            L.acquire()
            try: return f(*a, **k)
            finally: L.release()
        locked.__name__ = f.__name__
        return locked
    return lock_around
class X(object):
    CL = threading.Lock()
    @withlock(CL)
    def amethod(self):
        ...
        ...
```

Always-fresh defaults

```
def always_fresh_defaults(f):
    from copy import deepcopy
    defaults = f.func_defaults
    def refresher(*a, **k):
        f.func_defaults = deepcopy(defaults)
        return f(*a, **k)
    return refresher
```

```
@always_fresh_defaults
def packitem(item, pack=[]):
    pack.append(item)
    return pack
```

A property-packer

```
def prop(f): return property(*f())

class Rectangle(object):
    def __init__(self, x, y):
        self.x, self.y = x, y
    @prop
    def area():
        def get(self): return self.x*self.y
        def set(self, v):
            ratio = math.sqrt(v/self.area)
            self.x *= ratio
            self.y *= ratio
        return get, set
```

A generic decorator

```
def processedby(hof):  
    def processedfunc(f):  
        def wrappedfunc(*a, **k):  
            return hof(f, *a, **k)  
        wrappedfunc.__name__ = f.__name__  
        return wrappedfunc  
    return processedfunc
```

```
# e.g., hof might be s/thing like...:  
def tracer(f, *a, **k):  
    print '%s(%s,%s)' % (f, a, k),  
    r = f(*a, **k)  
    print '->', repr(r)  
    return r
```

Metaclasses

- ⦿ Every class statement uses a metaclass
 - ⦿ mostly type (or types.ClassType)
 - ⦿ no hassle, no problem, no issue
- ⦿ but, you can make a **custom** metaclass

Semantics of class

```
class X(abase, another):  
...classbody...
```

==>

1. execute ...classbody... building a dict D
2. identify metaclass M
 - 2.1 __metaclass__ in D
 - 2.2 leafmost metaclass among bases
(metatype conflict may be diagnosed)
 - 2.3 if no bases, __metaclass__ global
 - 2.4 last ditch, types.ClassType (old!)
3. X = M('X', (abase, another), D)
in whatever scope for class statement

Make a class on the fly

```
bunch = type('bunch', (), dict(foo=23, bar=42, baz=97))
```

is like...:

```
class bunch(object):  
    foo=23  
    bar=42  
    baz=97
```

```
# but may be handier (runtime-given name,  
# bases, and/or dictionary...).
```

A tiny custom metaclass

```
class MetaRepr(type):
    def __repr__(cls):
        C = cls.__class__          # leaf metaclass
        N = cls.__name__
        B = cls.__bases__
        D = cls.__dict__
        fmt = '%s(%r, %r, %r)'
        return fmt % (C, N, B, D)
```

Make accessor methods

```
class M(type):
    def __new__(cls, N, B, D):
        for attr in D.get('__slots__', ()):
            if attr.startswith('_'):
                def get(self, attr=attr):
                    return getattr(self, attr)
                get.__name__ = 'get' + attr[1:]
                D['get' + attr[1:]] = get
        return super(M, cls).__new__(N, B, D)
```

```
class Point:
    __metaclass__ = M
    __slots__ = '_x', '_y'
```

Tracking instances

```
from weakref import WeakValueDictionary

class mIT(type):
    def __init__(cls, N, B, D):
        super(mIT, cls).__init__(N, B, D)
        cls._inst = WeakValueDictionary()
        cls._numcreated = 0
    def __call__(cls, *a, **k):
        inst = super(mIT, cls).__call__(N, B, D)
        cls._numcreated += 1
        cls._inst[cls._numcreated] = inst
        return inst
    def __instances__(cls):
        return cls._inst.values()
```

Metatype conflicts

```
class meta_A(type): pass  
class meta_B(type): pass  
class A: __metaclass__ = meta_A  
class B: __metaclass__ = meta_B
```

```
class C(A, B): pass
```

```
# no leafmost metaclass -> conflict
```

```
# manual metatype conflict resolution:  
class meta_C(meta_A, meta_B): pass  
class C(A, B): __metaclass__ = meta_C
```

Removing redundancy

```
def uniques(sequence, skipset):
    for item in sequence:
        if item not in skipset:
            yield item
            skipset.add(item)
```

```
def no_redundant(classes):
    reds = set([types.ClassType])
    for c in classes:
        reds.update(inspect.getmro(c)[1:])
    return tuple(uniques(classes, reds))
```

The "no conflict" metaclass

```
def _noconf(bases, L, R):
    metas = L + tuple(map(type, bases)) + R
    metas = no_redundant(metas)
    if not metas: return type
    elif len(metas)==1: return metas[0]
    for m in metas:
        if not issubclass(m, type):
            raise TypeError, 'NTR %r' % m
    n = '_'.join(m.__name__ for m in metas)
    return classmaker()(n, metas, {})
def classmaker(L=(), R=()):
    def maker(n, bss, d):
        return _noconf(bss, L, R)(n, bss, d)
    return maker
```

Using noconf.py

```
class meta_A(type): pass  
class meta_B(type): pass  
class A: __metaclass__ = meta_A  
class B: __metaclass__ = meta_B
```

```
import noconf  
class C(A, B):  
    __metaclass__ = noconf.classmaker()
```